

# WarmTouch 22

An interactive multitouch display with built-in PC, based on AOPEN Digital Engine technology. The display is built in an aluminium casing designed to handle the rigors of intense use in a variety of scenarios.

- + IP65 grade dust & waterproof panel
- + Full HD display, with ideal viewing angle for both portrait and landscape orientation
- + All function keys are supported with a security lock, making it the ideal system for public environments



## WT22M-RHI

**Dimensions** 533 x 333 x 61.2 mm (W x H x D)

**Weight** 7.4kg

**Mass Storage** 2.5" SATA II HDD x1  
(optional 2.5" SATA SSD x1)

**CPU** Intel® 2nd and 3rd generation Intel® Core™ i3, i5, i7 mobile processor TDP≤35W

**Chipset** Intel® QM67

**Memory** Supports: 2 x DDRIII SO-DIMM (Max 8G)

**LAN** Dual Intel Gigabit Ethernet  
10/100/1000

**Audio** Realtek ALC886

**Mini-Card Slot** Full size x1 (support mSATA), Half size x1

**LCD** Default Resolution : 21.5" (1920 x 1080)  
Maximum Brightness : 250 Nits

**Aspect Ratio/Resolution** 16:9/Full HD

Supports:



### Touch Panel

AMR Multi Touch Surface, 4 Wire, 10 points Resistive  
Pencil Hardness 3H per ASTM D3363  
Pen Hitting: more than 1,000,000 times (loading 250g)

### Speakers

Built-in 2W Stereo Speaker

### Webcam

Built-in 1.3M

### Button/Indicator

Power Button, Monitor Function Buttons,  
HDD indicator (red)  
Power indicator (blue)

### System I/O

DC 19V Jack x1  
COM Port x4  
PC VGA Out Port x1  
Monitor VGA In Port x1  
GbE RJ45 LAN Jack x2  
USB 2.0 x6  
Printer Port x1  
RJ-11 Port x1  
5.1CH Audio: Audio Line-in x1, Line-out x1, Mic-in x1  
Kensington Lock Hole x1

### Front Panel Watchdog Timer

IP65 grade Dust- & Waterproof

1 sec ~ 255 sec

### Accessories

Wall Mount Kit x1  
90W Power Adapter x1  
Power Cord x1  
Utilities & Drivers CD x1